

Material Safety Data Sheet



1,1-Dichloro-2,2,2,-Trifluoroethane (Halocarbon R-123)

Section 1. Chemical product and company identification

Product Name : 1,1-Dichloro-2,2,2,-Trifluoroethane (Halocarbon R-123)
Supplier : AIRGAS INC., on behalf of its subsidiaries
259 North Radnor-Chester Road
Suite 100
Radnor, PA 19087-5283
1-610-687-5253
Product use : Synthetic/Analytical chemistry.
MSDS# : 001084
Date of Preparation/Revision : **3/14/2007.**
In case of emergency : 1-866-734-3438

Section 2. Hazards identification

Physical state : Gas.
Emergency overview : Warning!
CONTENTS UNDER PRESSURE.
MAY CAUSE EYE IRRITATION.
Avoid contact with eyes. Do not puncture or incinerate container. Wash thoroughly after handling.
Contact with rapidly expanding gases can cause frostbite.
Routes of entry : Inhalation,Dermal,Eyes
Potential acute health effects
Eyes : Moderately irritating to the eyes.
Skin : Slightly irritating to the skin.
Inhalation : Acts as a simple asphyxiant.
Ingestion : Ingestion is not a normal route of exposure for gases
Potential chronic health effects : **CARCINOGENIC EFFECTS** Not available.
MUTAGENIC EFFECTS Not available.
TERATOGENIC EFFECTS: Not available.
Medical conditions aggravated by overexposure : Acute or chronic respiratory conditions may be aggravated by overexposure to this gas.
See toxicological Information (section 11)

Section 3. Composition, Information on Ingredients

<u>Name</u>	<u>CAS number</u>	<u>% Volume</u>	<u>Exposure limits</u>
1,1-Dichloro-2,2,2,-Trifluoroethane (Halocarbon R-123)	306-83-2	100	AIHA WEEL (United States, 1/2004). CEIL: 5 ppm Form: All forms TWA: 50 ppm 8 hour(s). Form: All forms

Section 4. First aid measures

No action shall be taken involving any personal risk or without suitable training.If fumes are still suspected to be present, the rescuer should wear an appropriate mask or a self-contained breathing apparatus.It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin contact : Wash with soap and water. Get medical attention if irritation develops.
Frostbite : Try to warm up the frozen tissues and seek medical attention.
Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

1,1-Dichloro-2,2,2-Trifluoroethane (Halocarbon R-123)

Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.

Section 5. Fire fighting measures

Flammability of the product : Non-flammable.

Fire fighting media and instructions : Use an extinguishing agent suitable for surrounding fires.

If involved in fire, shut off flow immediately if it can be done without risk. Apply water from a safe distance to cool container and protect surrounding area.

No specific hazard.

Special protective equipment for fire-fighters : Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full facepiece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Shut off gas supply if this can be done safely. Isolate area until gas has dispersed.

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 7. Handling and storage

Handling : Avoid contact with eyes. Do not puncture or incinerate container. Wash thoroughly after handling. High pressure gas. Use equipment rated for cylinder pressure. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

Storage : Keep container tightly closed. Keep container in a cool, well-ventilated area. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52 °C (125 °F).

Section 8. Exposure Controls, Personal Protection

Engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.

Personal protection

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

The applicable standards are (US) 29 CFR 1910.134 and (Canada) Z94.4-93

Hands : Chemical-resistant, impervious gloves or gauntlets complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Personal protection in case of a large spill : A self-contained breathing apparatus should be used to avoid inhalation of the product.

Consult local authorities for acceptable exposure limits.

1,1-Dichloro-2,2,2-Trifluoroethane (Halocarbon R-123)

Section 9. Physical and chemical properties

Molecular weight	: 152.93 g/mole
Molecular formula	: C ₂ HCl ₂ F ₃
Boiling/condensation point	: 28°C (82.4°F)
Melting/freezing point	: -107°C (-160.6°F)
Critical temperature	: Not available.
Vapor pressure	: 11.4 psia
Vapor density	: 5.3 (Air = 1)
Specific Volume (ft³/lb)	: 2.51889
Gas Density (lb/ft³)	: 0.397

Section 10. Stability and reactivity

Stability and reactivity	: The product is stable.
Hazardous decomposition products	: These products are halogenated compounds, hydrogen chloride, hydrogen fluoride.

Section 11. Toxicological information

<u>Ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
1,1-Dichloro-2,2,2,- Trifluoroethane (Halocarbon R-123)	LC50	32000 ppm (4 hour(s))	Inhalation	Rat
	LC50	74000 ppm (1 hour(s))	Inhalation	Mouse

Other toxic effects on humans : Not considered to be toxic for humans.

Specific effects

Carcinogenic effects	: No known significant effects or critical hazards.
Mutagenic effects	: No known significant effects or critical hazards.
Reproduction toxicity	: No known significant effects or critical hazards.


Section 12. Ecological information

Products of degradation	: These products are carbon oxides (CO, CO ₂) and water, halogenated compounds.
Toxicity of the products of biodegradation	: The products of degradation are more toxic than the product itself.
Environmental fate	: Not available.
Environmental hazards	: No known significant effects or critical hazards.
Toxicity to the environment	: Not available.



Section 13. Disposal considerations

Product removed from the cylinder must be disposed of in accordance with appropriate Federal, State, local regulation. Return cylinders with residual product to Airgas, Inc. Do not dispose of locally.

Section 14. Transport information

<u>Regulatory information</u>	<u>UN number</u>	<u>Proper shipping name</u>	<u>Class</u>	<u>Packing group</u>	<u>Label</u>	<u>Additional information</u>
DOT Classification	UN1078	Refrigerant gases, n.o.s. (2,2-dichloro- 1,1,1-trifluoroethane (hfc-123))	2.2	Not applicable (gas).		-

1,1-Dichloro-2,2,2-Trifluoroethane (Halocarbon R-123)

TDG Classification	UN1078	Refrigerant gases, n.o.s. (2,2-dichloro-1,1,1-trifluoroethane (hfc-123))	2.2	Not applicable (gas).		Explosive Limit and Limited Quantity Index 0.125 Passenger Carrying Road or Rail Index 75
Mexico Classification	UN1078	Refrigerant gases, n.o.s. (2,2-dichloro-1,1,1-trifluoroethane (hfc-123))	2.2	Not applicable (gas).		-

Section 15. Regulatory information

United States

U.S. Federal regulations : TSCA 8(b) inventory: 2,2-dichloro-1,1,1-trifluoroethane (hfc-123)
 SARA 302/304/311/312 extremely hazardous substances: No products were found.
 SARA 302/304 emergency planning and notification: No products were found.
 SARA 302/304/311/312 hazardous chemicals: No products were found.
 SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.
 Clean Water Act (CWA) 307: No products were found.
 Clean Water Act (CWA) 311: No products were found.
 Clean air act (CAA) 112 accidental release prevention: No products were found.
 Clean air act (CAA) 112 regulated flammable substances: No products were found.
 Clean air act (CAA) 112 regulated toxic substances: No products were found.

SARA 313

	<u>Product name</u>	<u>CAS number</u>	<u>Concentration</u>
Form R - Reporting requirements	: 1,1-Dichloro-2,2,2,-Trifluoroethane (Halocarbon R-123)	306-83-2	100
Supplier notification	: 1,1-Dichloro-2,2,2,-Trifluoroethane (Halocarbon R-123)	306-83-2	100

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations : No products were found.

Canada

WHMIS (Canada) : Not controlled under WHMIS (Canada).
 CEPA DSL: 2,2-dichloro-1,1,1-trifluoroethane (hfc-123)

Section 16. Other information

United States

Label Requirements : CONTENTS UNDER PRESSURE.
 MAY CAUSE EYE IRRITATION.

Canada


Label Requirements : Not controlled under WHMIS (Canada).

Hazardous Material Information System (U.S.A.)

Health	1
Fire hazard	0
Reactivity	0
Personal protection	C

1,1-Dichloro-2,2,2-Trifluoroethane (Halocarbon R-123)

National Fire Protection Association (U.S.A.) :



Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.